

INNO-SEAL FOX C370

Machinery and Equipment Cleaning Agents

Description

FOX C370, is a cleaning material used in the cleaning of machinery and equipment used in Polyurea systems, polyurethane or epoxy resin products.

Fields of Application

- In the cleaning of machines used in **FOX PURMAX® SPRAYTEC** series products,
- Used for cleaning parts exposed to contact with polyurethane or epoxy resin products.

Advantages

- It has a good cleaning effect.

Technical Properties

Density	0,95±0,05 gr/cm ³
Color	Transparent

Application for Polyurea Machine

First, the polyurea machine is turned off and the pressure is reset. A and B component containers used in the application are separated from the system. **FOX C370** is connected instead of the A and B component containers separated from the system. **FOX C370** is drawn from both lines and circulated in the machine. Wait 5-10 minutes for the residues in the system to dissolve completely. If the machine supports gun cleaning, **FOX C370** is also passed through the gun part. If Gun Cleaning is not supported, all parts are brushed and kept in **FOX C370**. After the cleaning process is completed, DOP oil is circulated in the machine.

Watch Points

- Keeping **FOX C370** in the system for a long time may damage the gasket and sealing elements.
- **Never bring FOX C370 into contact with polyurea resins**, gelation may occur.

Package

6 lt/tin

Shelf Life

When stored correctly at room temperature, away from direct sunlight, between +5°C and +30°C, the shelf life is 12 months from the date of manufacture. Opened material should be used as soon as possible.

Storage

It should be stored in its unopened original packaging, in a cool and dry environment, protected from frost. For short-term storage, maximum 3 pallets should be stacked on top of each other and shipment should be made on a first-in, first-out basis. For long term storage, pallets should not be stacked on top of each other.

Safety Precautions

It is dangerous to approach the storage and application areas with fire. Storage and application areas should be ventilated. During the application, work clothes, protective gloves, goggles, masks in accordance with the occupational health and safety rules should be used. During storage and application, it should not be contacted with the skin and eyes, should be washed immediately with plenty of water and soap, and if swallowed, seek medical attention immediately. Food and drink materials should not be brought to the application areas. It should be stored out of the reach of children.

For detailed information, please refer to the Material Safety Data Sheet.

Disclaimer

The data contained in this technical document is based on our scientific and practical knowledge. Fox Bau Yapı Kimyasalları A.Ş. is only responsible for the quality of the product. Our company cannot be held responsible for the consequences that may occur due to misuse and/or other than the written suggestions about where and how the product will be used. For detailed information, the safety data sheet and technical data sheet should be consulted or our company officials should be contacted.

