

Product Technical Sheet Revision Date: 22.10.2019 Revision No: 4

INNO-CARE FOX CLEANER MULTI FR 500

Universal Cleaner

Description

FOX CLEANER MULTI FR 500 is extremely effective universal cleaning material used to remove stains and dirt on surfaces such as ceramic, tile, cement and silicone joint etc. It containing inorganic acid and does not containing detergent based; ozone, solvent, heavy toxic metals and chromates.

Fields of Application

- · Indoors and outdoors, in horizontal and vertical applications,
- · In the cleaning of molds and bacteria in silicone joints,
- · In the cleaning of lime, fungus and moss in swimming pools,
- · Effective cleaning of dirt on surfaces such as ceramic, tiles, marble, granite,
- Effective cleaning of dirt on surfaces such as natural stone, travertine, cotto and brick,
- It is used for effective cleaning of bacteria, fungi and algae deposits on many surfaces.

Advantages

- Hygienic,
- · Cleaning material used to remove stains and dirt quickly and effectively,
- Operation is quick, efficient and ready.
- It is suitable for use in ceramic, tile, cement based and silicon joint like places,
- · Cleans dirt, mold, bacteria, fungus and mosses, provides hygiene,
- Easy to apply and use,
- Dirt and bacteria form joints are cleaned without irritation.

Technical Data

Structure of Material	Acidic Detergent
Density	1,0 gr/cm ³
Color	Transparent
Odor	Blueberry
Application Temperature	+5°C/30°C

The values above are given for +23°C and 50% relative humidity. While higher temperatures shorten the period, lower temperatures extend it.

Application Procedure Preparation of the Substrate

Care should be taken to ensure that the surface is dry. On soft and delicate surfaces, a small field trial should be done before application and care should be taken not to make contact with the product cement based joint fillers.

Application

On extreme and very dirty surfaces the application can be repeated several times. FOX CLEANER MULTI FR 500 is rubbed with a hard-bristled brush or hard-surface sponge after 5 minutes of spraying to the surface. The surfaces should be rinsed with water without allowing the drying.

Consumption

Valuable

Package

5 kg plastic drums, 500 ml Spray Bottle (12 pieces / parcel)

Shelf Life

Shelf life is 24 months from the date of production when stored properly at +5 °C to +30 °C at room temperature, away from direct sunlight.

Storage

The product should be stored in its original package, in a cool and dry place protected from frost. For short term storage, maximum 3 palettes should be placed on top of each other and the shipment should be made on a 'first come, first go' basis. Palettes should not be placed on top of each other during long term storage.



Merkez/Fabrika Organize Sanayi Bölgesi 1. Kısım 7. Cadde No:6 Döşemealtı/Antalya-TÜRKİYE Tel.: +90 (242) 221 42 50 • Faks : +90 (242) 221 42 55



Health and Safety Precautions

It is dangerous to approach the application sites with fire. Fresh air should be circulated in the storage and the application sites. During the application, a protective apparel, protective gloves, goggles and masks which comply with the Occupational Health and Safety Rules should be used. Due to the irritation effect of the uncured materials, the mixture should not come into contact with skin and eyes; in case of a contact, the affected area should be washed with plenty of water and soap; in case of swallowing, a physician should be consulted immediately. No food or beverages should be brought to the application area. The product should be stored and kept out of reach of children.

For detailed information please consult the Material Safety Data Sheet.

Disclaimer

The technical information given in this publication is based on the present state of our best scientific and practical knowledge. SARTECH Yapi Malzemeleri San. Tic. Ltd Şti.is only responsible for the quality of the product. SARTECH Yapi Malzemeleri San. Tic. Ltd Şti. is not responsible for results that may occur because the product is used other than advised and/or out of instructions regarding the place and the method of use. This technical form is valid only till a new version is implemented and nullifies the old ones.



Merkez/Fabrika Organize Sanayi Bölgesi 1. Kısım 7. Cadde No:6 Döşemealtı/Antalya-TÜRKİYE Tel.: +90 (242) 221 42 50 • Faks : +90 (242) 221 42 55