

INNO-FLOOR FOX CS810

Thinning and Cleaning Agent

Description

FOX CS810, is used as a thinning and cleaning agent.

Fields of Application

- In the thinning of **FOX PURFUGA FX145 PEBBLE** product,
- For thinning **FOX EPOTHANE®** and **FOX PURATHANE®** series products,
- Used for cleaning work equipment contaminated with epoxy or polyurethane.

Advantages

- It has a good cleaning effect.
- It has a good thinning effect.

Technical Properties

Density	0,87±0,05 gr/cm ³
Color	Transparent

Mixing Ratios

FOX PURFUGA FX145 PEBBLE, **FOX EPOTHANE®** and **FOX PURATHANE®** products, 1-3% of the packaging weight of the product used should be used **FOX CS810**.

Mixing

Mix the material to be thinned according to the information written in the technical documentation. Then add **FOX CS810** up to maximum 3% of the mixed product. Mix the material until homogeneous and apply the material quickly.

Hususlar Watch Points

- Excessive use of thinners may cause dusting, cracking, loss of chemical and mechanical strength.
- May not be compatible with all joint sealants - do not exceed the manufacturer's recommendation.
- Consume the mixture in a short time; pot-life of thinner-added products may be shorter.

Package

6 lt/tin
22 lt/tin
210 lt/barrel

Shelf Life

When stored correctly at room temperature, away from direct sunlight, between +5°C and +30°C, the shelf life is 12 months from the date of manufacture. Opened material should be used as soon as possible.

Storage

It should be stored in its unopened original packaging, in a cool and dry environment, protected from frost. For short-term storage, maximum 3 pallets should be stacked on top of each other and shipment should be made on a first-in, first-out basis. For long term storage, pallets should not be stacked on top of each other.

Safety Precautions

It is dangerous to approach the storage and application areas with fire. Storage and application areas should be ventilated. During the application, work clothes, protective gloves, goggles, masks in accordance with the occupational health and safety rules should be used. During storage and application, it should not be contacted with the skin and eyes, should be washed immediately with plenty of water and soap, and if swallowed, seek medical attention immediately. Food and drink materials should not be brought to the application areas. It should be stored out of the reach of children.

For detailed information, please refer to the Material Safety Data Sheet.



www.foxbau.com

FOX BAU YAPI KİMYASALLARI ANONİM ŞİRKETİ

Merkez: Organize Sanayi Bölgesi 1. Kısım 7. Cadde No:6 Döşemealtı-ANTALYA/TÜRKİYE
Telefon: 0(242) 221 42 50 Fax: 0(242) 221 42 55
Şube 1: Kargalı Hanbabaosb Mah. Organize San. 10. Sk. No:6 Hendek-Sakarya/TÜRKİYE
Şube 2: Oyalı OSB Mahallesi 3. Cadde No:21 Eğil-Diyarbakır/TÜRKİYE
Web : www.foxbau.com E-mail : info@foxbau.com

Disclaimer

The data contained in this technical document is based on our scientific and practical knowledge. Fox Bau Yapı Kimyasalları A.Ş. is only responsible for the quality of the product. Our company cannot be held responsible for the consequences that may occur due to misuse and/or other than the written suggestions about where and how the product will be used. For detailed information, the safety data sheet and technical data sheet should be consulted or our company officials should be contacted.



FOX BAU YAPI KİMYASALLARI ANONİM ŞİRKETİ

Merkez: Organize Sanayi Bölgesi 1. Kısım 7. Cadde No:6 Döşemealtı-ANTALYA/TÜRKİYE
Telefon: 0(242) 221 42 50 Fax: 0(242) 221 42 55
Şube 1: Kargalı Hanbabaosb Mah. Organize San. 10. Sk. No:6 Hendek-Sakarya/TÜRKİYE
Şube 2: Oyalı OSB Mahallesi 3. Cadde No:21 Eğil-Diyarbakır/TÜRKİYE
Web : www.foxbau.com E-mail : info@foxbau.com