

INNO-DECO

FOX EPOTHANE® FILLER TF

Epoxy Terrazzo Filler

Description

FOX EPOTHANE® FILLER TF is specially developed epoxy terrazzo filler for **FOX ZEUGMA EPOXY TERRAZZO** System Matrix.

Fields of Application

- **FOX ZEUGMA EPOXY TERRAZZO** is used in system matrix as a filler.

Advantages

- Enables epoxy terrazzo system to be applied easier,
- It provides the filling of the gaps of aggregates with the matrix.

Technical Features

Material Structure	Quartz
Color	White

The above values are given for + 23 ° C and 50% relative humidity. High temperatures shorten the time, low temperatures increase the time.

Surface Quality

Concrete substrates to be applied must have a strong and sufficient compressive strength (at least 25 N/mm²), tensile strength at least 1.5 N/mm², humidity should be maximum 4%, ground temperature minimum +8°C. In addition, it should be noted that the dew point of the ground is above +3°C. The substrate should be clean, dry and free from all kinds of dirt, oil, grease, coating and surface curing materials etc.

Application Procedure

Mixing

FOX EPOTHANE® FILLER TF is mixed into the **FOX EPOTHANE® BASECOAT TERRAZZO** by adding it as specified in the **FOX ZEUGMA EPOXY TERRAZZO** System. The mixture is added on the aggregates in the terrazzo mixing mixer bowl and mixed until it becomes homogeneous again (30-45 seconds).

Consumption

Variable

Package

25 kg bag

Shelf Life and Storage

The product should be stored in its unopened original packaging in a dry environment. If the specified storage conditions are maintained, the shelf life is unlimited. Pallets must not be stacked during storage. Shipment should be carried out according to the FIFO (First In – First Out) principle.

Safety Precautions

It is dangerous to approach storage and application areas with open flames. Storage and application areas must be well ventilated.

During application, appropriate workwear, protective gloves, safety goggles, and masks must be used in accordance with occupational health and safety regulations. Avoid contact with skin and eyes during storage and application; in case of contact, wash immediately with plenty of water and soap. In case of ingestion, seek medical attention immediately. Food and beverages must not be brought into application areas. Keep out of reach of children.

For detailed information, refer to the Safety Data Sheet (Material Safety Data Sheet).

Liability

The data provided in this technical document is based on our scientific and practical knowledge. Fox Bau Yapı Kimyasalları A.Ş. is only responsible for the quality of the product. Our company cannot be held liable for any results arising from improper use and/or applications outside our written recommendations. For further information, please refer to the Safety Data Sheet and Technical Data Sheet or contact our authorized personnel.



www.foxbau.com

FOX BAU YAPI KİMYASALLARI ANONİM ŞİRKETİ

Merkez: Organize Sanayi Bölgesi 1. Kısım 7. Cadde No:6 Döşemealtı-ANTALYA/TÜRKİYE

Telefon: 0(242) 221 42 50

Fax: 0(242) 221 42 55

Şube 1: Kargalı Hanbabaosb Mah. Organize San. 10. Sk. No:6 Hendek-Sakarya/TÜRKİYE

Şube 2: Oyalı OSB Mahallesi 3. Cadde No:21 Etil-Diyarbakır/TÜRKİYE

Web: www.foxbau.com

E-mail: info@foxbau.com