

INNO-FEES

FOX FILL&FINISH

Ready-to-Use Light Filler

Description

FOX FILL&FINISH, acrylic-based, ready-to-use, multipurpose filler and surface leveling material developed for interior applications.

Fields of Application

- Filling and leveling drywall joints
- Repairing nail, screw marks, and surface imperfections on drywall
- Leveling filler for plaster or cement-based surfaces before painting or wallpapering
- Skim coat for plaster or drywall surfaces
- Surface preparation for interior painting
- Used with joint tape to fill gaps and cracks

Advantages

- Ready-to-use
- Multipurpose
- Easy to apply
- Easy to sand
- Lightweight
- High adhesion
- Dust-free after drying

Technical Properties

Density	1,42±0,05 g/cm ³
Colour	Off-white
Drying Time	~1 day

The above values are given for +23°C and 50% relative humidity. High temperatures shorten the time, low temperatures lengthen the time.

Application Procedure

Substrate Preparation

The surface to be treated must be free of loose particles, grease, oil, dirt, or any residues that may reduce adhesion. Materials such as putty or paper residues must be removed. Drywall must be securely fixed to clean, dry, and dust-free substrates, ensuring that joints are free of dust.

Mixing

Before use, **FOX FILL&FINISH** should be mixed with an electric mixer at 400–600 rpm.

Dilution

FOX FILL&FINISH can be diluted with up to 10% water.

Application

Apply **FOX FILL&FINISH** using a putty knife, wide spatula, scraper, or similar tools. Drywall joints, screw and nail marks should be properly filled. Screw heads must be covered. For joint gaps, using drywall joint tape is recommended. If applying multiple coats, wait until the previous coat is fully dry before applying the next.

Cleaning of Tools

Clean all tools and equipment with water immediately after use.

Consumption

For Q1* surface quality joint filling: ~0.200 kg/m²

For Q2** surface quality joint filling: ~0.100 kg/m²

For skim coating over Q2 joint filling to achieve Q4*** surface quality (1 mm thickness): ~1.10 kg/m²

*Q1 Surface Quality: Placement of joint tape, filling of Alçıpan® joints, and covering visible screw heads.

**Q2 Surface Quality: Includes Q1 and additional surface treatment (fine filling, finishing) to ensure smooth transitions between Alçıpan® panels.

***Q4 Surface Quality: Covers Q3 standard treatment, wide-area joint coverage, application of appropriate material over the entire surface, and skim coating (layer thickness above 1 mm). Suitable for smooth surfaces like wallpaper or medium-gloss paints.



www.foxbau.com

FOX BAU YAPI KİMYASALLARI ANONİM ŞİRKETİ

Merkez : Organize Sanayi Bölgesi 1. Kısım 7. Cadde No:6 Döşemealtı-ANTALYA/TÜRKİYE
Telefon : 0(242) 221 42 50 Fax: 0(242) 221 42 55
Şube 1 : Kargalı Hanbabaosb Mah. Organize San. 10. Sk. No:6 Hendek-Sakarya/TÜRKİYE
Şube 2 : Oyali OSB Mahallesi 3. Cadde No:21 Eğil-Diyarbakır/TÜRKİYE
Web : www.foxbau.com E-mail : info@foxbau.com

Watch Points

- Do not apply at temperatures below +10°C.
- Hot weather shortens drying time, while cold weather increases it.
- For thick layer applications, longer drying times may occur depending on temperature and humidity.

Package

20 kg/bucket

Shelf Life and Storage

Unopened, it can be stored for 12 months in a cool, dry place, protected from frost and direct sunlight. Close the container immediately after use to prevent air ingress. It must be stored in its unopened original packaging, in a cool, dry area protected from frost. To prevent damage to the packaging integrity, pallets must not be stacked and should be arranged in a single layer. During shipments, the first-in, first-out principle must be followed.

Safety Precautions

It is dangerous to approach the storage and application areas with fire. Storage and application areas should be ventilated. During the application, work clothes, protective gloves, goggles, masks in accordance with the occupational health and safety rules should be used. During storage and application, it should not be contacted with the skin and eyes, should be washed immediately with plenty of water and soap, and if swallowed, seek medical attention immediately. Food and drink materials should not be brought to the application areas. It should be stored out of the reach of children.

For detailed information, please refer to the Material Safety Data Sheet.

Disclaimer

The data contained in this technical document is based on our scientific and practical knowledge. Fox Bau Yapı Kimyasalları A.Ş. is only responsible for the quality of the product. Our company cannot be held responsible for the consequences that may occur due to misuse and/or other than the written suggestions about where and how the product will be used. For detailed information, the safety data sheet and technical data sheet should be consulted or our company officials should be contacted.



www.foxbau.com

FOX BAU YAPI KİMYASALLARI ANONİM ŞİRKETİ

Merkez : Organize Sanayi Bölgesi 1. Kısım 7. Cadde No:6 Döşemealtı-ANTALYA/TÜRKİYE
Telefon : 0(242) 221 42 50 Fax: 0(242) 221 42 55
Şube 1 : Kargalı Hanbabaosb Mah. Organize San. 10. Sk. No:6 Hendek-Sakarya/TÜRKİYE
Şube 2 : Oyali OSB Mahallesi 3. Cadde No:21 Eğil-Diyarbakır/TÜRKİYE
Web : www.foxbau.com E-mail : info@foxbau.com