

# INNO-PAINT

## FOX INOVA CHANTIER

### Economic Matte Interior Paint

#### Description

**FOX INOVA CHANTIER**, is a water-based, styrene-acrylic, economical, matte paint designed for interior and construction site applications.

#### Fields of Application

- Interior plaster surfaces
- Concrete surfaces
- Interior walls
- Living spaces such as living rooms and bedrooms

#### Advantages

- Easy to apply
- Spreads well on the surface
- Provides good coverage
- Allows the surface to breathe
- No splashing or dripping
- Environmentally friendly
- Low odor
- Washable

#### Technical Properties

Density		1.52 gr/cm <sup>3</sup>
Colour		White
Glossiness	EN 13300	G4 Super-matte
Touch Dry		20 min
Fully Dry		6 hr

*The above values are given for +23°C and 50% relative humidity. High temperatures shorten the time, low temperatures lengthen the time.*

#### Application Procedure

##### Substrate Preparation

The surface to be painted must be free of loose particles, grease, oil, dirt, dust, or any residues that may reduce adhesion. The surface can be dry or slightly damp and may be painted or unpainted. On previously painted surfaces with peeling areas, these must be cleaned and leveled using repair mortars such as **FOX FASTMORTAR FC245** or **FOX BASEMOR FC205**.

##### Primering

###### Old Mineral Plasters and Concrete

Lightly absorbent, smooth surfaces: prime with **FOX DECODUR PRIMER**  
Porous, absorbent, slightly sandy surfaces: prime with **FOX PRIMERA® FL220**

###### Old Matte Coatings

Moderately absorbent surfaces: prime with **FOX DECODUR PRIMER** diluted with max. 3% water  
Porous, absorbent, slightly sandy surfaces: prime with **FOX PRIMERA® FL220** diluted 1:1 with water

###### Glossy Surfaces

Prime with **FOX UNIPRIMER FL555**.

###### Wallpaper

Do not apply paint directly on wallpaper. Remove wallpaper completely. If the underlying surface is powdery plaster, lime, or whitewash, remove it entirely down to a sound substrate, then apply fresh plaster followed by **FOX PRIMERA® FL220** diluted 1:1.

###### Gypsum Plaster Surfaces

Prime with **FOX PRIMERA® FL220** diluted 1:1 with water



www.foxbau.com

#### FOX BAU YAPI KİMYASALLARI ANONİM ŞİRKETİ

Merkez : Organize Sanayi Bölgesi 1. Kısım 7. Cadde No:6 Döşemealtı-ANTALYA/TÜRKİYE  
Telefon : 0(242) 221 42 50 Fax : 0(242) 221 42 55  
Şube 1 : Kargalı Hanbabaosb Mah. Organize San. 10. Sk. No:6 Hendek-Sakarya/TÜRKİYE  
Şube 2 : Oyali OSB Mahallesi 3. Cadde No:21 Eğil-Diyarbakır/TÜRKİYE  
Web : www.foxbau.com E-mail : info@foxbau.com

## Mixing

Before use, mix **FOX INOVA CHANTIER** with an electric mixer at 400–600 rpm until homogeneous.

## Dilution

**FOX INOVA CHANTIER** can be diluted with a maximum of 10% water.

## Application

After the primer has dried, apply **FOX INOVA CHANTIER** using a roller or spray machine. Use a brush for corners and edges. Apply the second coat after the first coat has dried (minimum 6 hours) using the same method.

## Cleaning of Tools

Clean tools and equipment with water immediately after use.

## Consumption

One coat:  $\sim 0.100 \text{ L/m}^2$  ( $\sim 0.150 \text{ kg/m}^2$ ), Two coats:  $\sim 0.150 \text{ L/m}^2$  ( $\sim 0.230 \text{ kg/m}^2$ ). Actual consumption depends on surface conditions and should be determined by testing.

## Watch Points

- Apply wet-on-wet in a single pass to avoid overlaps.
- Protect surfaces from rain, water, mechanical impacts, and other external factors for 24 hours during and after application.
- Close container lids during breaks.
- Ensure proper ventilation and use mask, gloves, and protective goggles.
- Do not apply paint on dirty or damp surfaces. Prepare the surface according to the paint type.
- Avoid application in extremely hot or cold conditions (recommended air and surface temperature:  $+5^\circ\text{C}$  to  $+30^\circ\text{C}$ ).
- When cleaning stains on walls, clean the entire wall to avoid local differences in gloss.
- For newly plastered or raw concrete surfaces, the first application should be done at least 28 days after construction.
- Follow the dilution rates on the product label. Excessive dilution may reduce coverage and cause roller marks or waviness.
- Insufficient dilution may result in a thick application, which can cause cracking.
- Do not add powders or liquids to the paint, and do not exceed the recommended dilution.
- When painting, first make cuts around doors, windows, and ceiling-wall junctions, then continue rolling without interruption.

## Package

12.5 L (19 kg) Bucket

## Shelf Life

Unopened, it can be stored for 12 months in a cool, dry place, protected from frost and direct sunlight. Close the container immediately after use to prevent air ingress.

## Storage

It should be stored in its unopened original packaging, in a cool and dry environment, protected from frost. For short-term storage, maximum 3 pallets should be stacked on top of each other and shipment should be made on a first-in, first-out basis. For long term storage, pallets should not be stacked on top of each other.

## Safety Precautions

It is dangerous to approach the storage and application areas with fire. Storage and application areas should be ventilated. During the application, work clothes, protective gloves, goggles, masks in accordance with the occupational health and safety rules should be used. During storage and application, it should not be contacted with the skin and eyes, should be washed immediately with plenty of water and soap, and if swallowed, seek medical attention immediately. Food and drink materials should not be brought to the application areas. It should be stored out of the reach of children.

For detailed information, please refer to the Material Safety Data Sheet.

## Disclaimer

The data contained in this technical document is based on our scientific and practical knowledge. Fox Bau Yapı Kimyasalları A.Ş. is only responsible for the quality of the product. Our company cannot be held responsible for the consequences that may occur due to misuse and/or other than the written suggestions about where and how the product will be used. For detailed information, the safety data sheet and technical data sheet should be consulted or our company officials should be contacted.



www.foxbau.com

## FOX BAU YAPI KİMYASALLARI ANONİM ŞİRKETİ

Merkez : Organize Sanayi Bölgesi 1. Kısım 7. Cadde No:6 Döşemealtı-ANTALYA/TÜRKİYE  
Telefon : 0(242) 221 42 50 Fax: 0(242) 221 42 55  
Şube 1 : Kargalı Hanbabaosb Mah. Organize San. 10. Sk. No:6 Hendek-Sakarya/TÜRKİYE  
Şube 2 : Oyali OSB Mahallesi 3. Cadde No:21 Eğil-Diyarbakır/TÜRKİYE  
Web : www.foxbau.com E-mail : info@foxbau.com