

INNO-FLOOR FOX PEBBLEDECK® AGREGA

Specially Selected Natural Colour Aggregate

Description

FOX PEBBLEDECK® AGREGA, are 2-4mm aggregates with different colours and rounded edges because of the abrasion of water in nature especially found around creeks and seaside.

Fields of Application

- Swimming pools,
- Ornamental pools.

Advantages

- Can be used in interiors and exteriors.
- It adds an aesthetic appearance to the surface.
- It can create different perceptions with aggregates used in different colours.

Technical Features

2-4 mm Natural Aggregate
Colour

Black Pearl, Black Onyx, Midnight Blue, Rain Forest, Spring Breeze, Ice Blue, Sunset Grey, Sea Pearl, Sandy Beach, White Pearl, Moonlight, Sky Blue

Surface Quality

Concrete substrates to be applied must have a strong and sufficient compressive strength (at least 25 N/mm²), tensile strength at least 1.5 N/mm², humidity should be maximum 4%, ground temperature minimum +8°C. In addition, it should be noted that the dew point of the ground is above +3°C. The substrate must be clean, dry and free from all kinds of dirt, oil, grease, coating and surface curing materials etc.

Application Procedure

Substrate Preparation

Concrete substrates to be applied should be prepared in such a way as to obtain an open porous surface by removing cement grout by using abrasive equipment (Shot Blasting, milling, diamond polishing etc.). Weak concrete pieces should be removed from the surface, small gaps, holes should be made completely open. The resulting dust should be cleaned with the help of an industrial vacuum cleaner. Sub-surface repairs, filling the gaps and levelling the surface should be done with **FOX SSL®** series levelling screed.

Coverage

Fox Pebbledeck Aggregate Floor 15 kg/m²
Fox Pebbledeck Aggregate Wall 10 kg/m²

Package

25 kg bag

Storage

It must be stored in its unopened original packaging. For short term storage, maximum 2 pallets should be placed on top of each other and shipment should be made with the first in, first out system. In long-term storage, pallets should not be placed on top of each other.

Safety Precautions

It is dangerous to approach the storage and application areas with fire. Storage and application areas should be ventilated. During the application, work clothes, protective gloves, goggles, masks in accordance with the occupational health and safety rules should be used. During storage and application, it should not be contacted with the skin and eyes, should be washed immediately with plenty of water and soap, and if swallowed, seek medical attention immediately. Food and drink materials should not be brought to the application areas. It should be stored out of the reach of children.

For detailed information, please refer to the Material Safety Data Sheet.



Disclaimer

The data contained in this technical document is based on our scientific and practical knowledge. SARTECH Yapı Malzemeleri San. ve Tic. Ltd. Sti is only responsible for the quality of the product. Except for the written suggestions about where and how the product will be used and / or results that may occur due to misuse, SARTECH Yapı Malzemeleri San. ve Tic. Ltd. Sti. cannot be held responsible. The responsibility for the correct application of our product lies with the user. Our company is only responsible for the quality of the product. This catalogue invalidates the information in the previous catalogue. Our company has the right to make changes in all kinds of information and content details in this catalogue. It is essential to check that the information in the catalogue is current and valid. All rights reserved.

