

INNO- PROOF FOX TRIPLETAPE 120

Three Layer, Two Sides Polypropylene Felt Coated, Alkali Resistant Insulating Tape

DESCRIPTION

FOX TRIPLETAPE 120 is a three layer, high-elastic, longitudinal rigid (non-stretchable) waterproofing tape with a special polypropylene (PP) felt coating on both sides.

FIELDS OF APPLICATION

- Wet volume (bathroom, balcony, terrace, roof, pool, industrial kitchens etc.) waterproofing applications,
- Horizontal and vertical joint and chamfer insulation,
- Insulation of shower channel surroundings and drain units,
- Ceramic and natural stone applications,

ADVANTAGES

- Easy and fast application,
- It is long lasting,
- Resistant to Freeze-Thaw cycle,
- Resistant to chemicals,
- Can be used at temperatures between -30°C and 90°C.
- Has forms designed to be used in interior corner, exterior corner, installation and floor drains.
- Can be used in applications exposed to a high degree of load or under constant positive pressure water.

TECHNICAL DATA

Structure of Material	Carrier (bottom and top) Coating	Polypropylene (PP) felt Highly flexible thermoplastic elastomer
Color		Gray
Breaking Load-Longitudinal	DIN EN ISO 527-3	120 N/15 mm
Breaking Load-Transverse	DIN EN ISO 527-3	25 N/15 mm
Elongation at Break - Longitudinal	DIN EN ISO 527-3	%70
Elongation at Break-Transverse	DIN EN ISO 527-3	%300
Puncture Pressure		2 bar
UV Resistance, min	DIN EN ISO 4892-2	≥500 hours
Thickness		0,66 mm

Chemical Resistance Table

Hydrochloric Acid %3	+	Lactic Acid %5	+	Sodium hypochlorite 0,3g/l	+
Sulfuric Acid %35	+	Potassium hydroxide%3/%20	+	Salt water (20g / l saltwater)	+
Citric Acid 100g/l	+				

+ = Durable; - = Nondurable; 0 = weak

PACKAGE

Roll Dimensions: 0,12*50 mt.

STORAGE

Store in cool and dry places, not exposed to sunlight. The most appropriate period of use is 24 months.



Disclaimer

The data contained in this technical document is based on our scientific and practical knowledge. SARTECH Yapı Malzemeleri San. ve Tic. Ltd Şti. is only responsible for the quality of the product. From the results that may occur due to misuse and other than written suggestions about where and how to use the product, SARTECH Yapı Malzemeleri San. ve Tic. Ltd Şti. cannot be held responsible. The responsibility of the correct application of our product belongs to the user. Our company is only responsible for the quality of the product. This technical form is valid only till a new version is implemented and nullifies the old ones. Our company has the right to make changes in all kinds of information and content details in this catalog. It is imperative to check that the information in the catalog is current and valid. All rights reserved.

